

Standard accessories:

- Trigger gun Easy Press
- Trigger gun with soft grip
- High-pressure hose 10 m
- Spray lance 850 mm
- Triple nozzle/Power nozzle manuell
- Triple nozzle (0°/25°/40°)
- Anti-twist system (AVS)
- Pressure switch control
- Stainless steel spray lance 850 mm



Order no.: 1.150-150.0

Technical data

Number of current phases (Ph)	1
Frequency (Hz)	50
Voltage (V)	230
Water flow rate (l/h)	300-600
Operating pressure (bar/MPa)	20-120/2-12
Max. pressure bar	160
Max. water feed temperature (°C)	up to 60
Connected load (kW)	2.8
Weight (kg)	29.5
Dimensions (L x W x H) (mm)	375x360x935

Cold water compact class

HD 6/12-4 C



Details

Description

Application

Features & Benefits

Accessories

Adapter for variable pressure spray lance

Adapter for variable pressure spray lance

For items 4.760-230 and 4.760-362 for mounting accessories to lance, M 24/18 x 1.5

Order no. 4.762-075.0



Angular spray lance

Bathroom and eaves gitter spray lance

With nozzle. Specially shaped for cleaning of eaves gutters and for hygienically cleaning WCs. Stainless steel.

Order no. 4.760-073.0



Automatic, self-winding hose reels

ABS wall fastening stainless steel

Swivelling wall bracket made of high-grade steel (for 2.641-866). This makes maximum flexibility and convenience possible when working with the HP hose.

Order no. 2.641-867.0



ABS hose reel stainless steel

High-grade, automatic steel hose reel. Especially suitable for use in the food industry. The material and finish provide for a corrosion-resistant, watertight capsuled sprung drive. Connection for HP hoses with nipple.

Order no. 2.641-866.0



Self-winding hose reel with swivel holder, stainless steel, 20 m

Automatic hose reel with swivel holder (high-grade steel)

Order no. 6.391-421.0



Automatic, self-winding hose reels

Swivel holder

ABS swivel holder for 2.639-919.0

Order no. 2.639-931.0



Hose drum, automatic, 20 m, coated

Hose reel, automatic, 20 m, coated

Order no. 2.639-919.0



Backflow check valve

Backflow preventer

To prevent detergent getting into the drinking water cycle in case of inlet at low-pressure. - hot water resistant up to 80 °C - tested according to IEC 60335-2-79 - integrated leakage protection

Order no. 2.641-374.0



Becher-Schaumlanze

Foam lance

Order no. 6.394-668.0



Boron carbide nozzle

Boron carbide nozzle, for machines as of 1000 l/h

In addition to nozzle packs. Very wear-resistant nozzle with boron carbide chuck for continuous-duty operation.

Order no. 6.415-084.0



Connector

Nozzle union / Screw union

For connecting HP nozzle and accessories directly to trigger gun (with nozzle union) – 1 x M 22 x 1.5 / 1 x M 18 x 1.5

Order no. 4.402-022.0



Coupling

Double pipe union

For connecting and extending HP hoses. 2 x M 22 x 1,5 connections, brass with rubber protector

Order no. 4.403-002.0



Dirt Blaster

Dirt Blaster

Order no. 4.767-100.0



Dirt blaster – changeover to low pressure cleaning agent intake

Dirt blaster - changeover to low pressure cleaning agent intake

Dirt blaster – rotating pencil jet – 10x cleaning power. Ceramic nozzle and bearing ring for long service life. Changeover to detergent intake (low pressure) max. 300 bar/30 MPa, 85 °C

Order no. 4.763-950.0



Dirt blaster – non-changeover

Dirt Blaster, not adjustable

Dirt blaster – rotating pencil jet – 10x cleaning power. Ceramic nozzle and bearing ring for long service life. Max. 300 bar/30 MPa, 85 °C

Order no. 4.763-988.0



Dreckfräser - umschaltbar auf Flachstrahl

Dirt blaster - changeover to fan jet

Dirt blaster – rotating pencil jet – 10x cleaning power. Ceramic nozzle and bearing ring for long service life. Changeover to high-pressure fan jet max. 300 bar/30 MPa, 85 °C

Order no. 4.763-956.0



Drum and tank cleaning

ABS barrel cleaner

The BC 14/12 is an spray system for the efficient interior cleaning of containers and barrels, specially oak barrels with a volume of between 225 and 600 litres. One cleaning cycle is completed within 36 seconds and every spot in the container is covered by a water jet. After cleaning is finished the BC 14/12 can easily and conveniently take up the dirty water. The transformer included with the BC 14/12 makes it possible to use it worldwide (110 - 240 V, 50 - 60 Hz). The nozzle kits included make possible use with high-pressure cleaners with a water volume of 600 to 1400 l / h. Electrical components are protected in accordance with IP 55.

Order no. 2.641-740.0



Easy Foam Set

Easy Foam Set with RM injector

HP foam system for use with. HD/HDS units for cleaning and disinfecting. Foam nozzle for connection to lance and HP chemical injector with precision 0-5% metering valve. The machine specific nozzle kit has to be ordered separately.

Order no. 2.640-691.0



Easy Press high-pressure gun with holding power reduction (KÄRCHER patent)

Easy Press high-pressure gun with soft grip insert

Easy Press HP trigger guns, for HP hoses NW 6 / NW 8 with swivel diameter 11 mm

Order no. 4.775-463.0



Fine-mesh water filter

Fine mesh water filter, 80 µm, R 3/4" + 1", with adapter

Mounted to machine inlet, 80 µm, with adapter R 3/4" / 1"

Order no. 4.730-102.0



Flexible spray lance

Jet pipe flexible

Infinitely variable adjustment of the angle of the spray lance from 20° - 140°. Especially suitable for cleaning difficult-to-reach areas such as roof gutters, car roofs, undercarriages or wheel cases.

Order no. 6.394-654.0



Foam nozzle mounting kit

Anbausatz Schaumdüse

For applying foam detergent in metered quantities in sanitary and food areas, or where long reaction time is necessary, mounts to spray lance in place of HP nozzle

Order no. 2.637-926.0



Food industry version

High-pressure hose, 15 m, DN 6, AVS trigger gun connection, food industry, grey

Food industry version, AVS connection in the pistol. NW 6/155 °C/250 bar

Order no. 6.390-445.0



Geka coupling

Geka coupling with female thread, R 3/4"

with female thread

Order no. 6.388-473.0



Geka coupling with hose liner, R 1/2"

with hose liner

Order no. 6.388-461.0



Geka coupling with hose liner, R 3/4"

with hose liner

Order no. 6.388-455.0



Hard surface cleaner FR 30

FR 30 hard surface cleaner

A rotating nozzle beam with KÄRCHER Power nozzles has an area coverage up to 10 times larger than conventional methods. Ceramic bearings, plastic cover for good manoeuvrability. Machine specific nozzle kit has to be ordered separately.

Max. 180 bar / 850 l/h / 60 °C

Order no. 2.641-065.0



Hard surface cleaner FR 30 ME

FR 30 ME hard surface cleaner

A rotating nozzle beam with KÄRCHER Power nozzles has an area coverage up to 10 times larger than conventional methods. Stainless steel version. Ceramic bearings. Integral vacuum connection. Machine specific nozzle kit has to be ordered separately. Max. 250 bar / 1100 l/h / 80 °C

Order no. 2.640-355.0



HP detergent injector

Detergent injector for high pressure

Cleaning agent dosage at high pressure 3 - 5 %

Order no. 3.637-170.0



HP nozzle spray angle 0°

HP nozzle spray angle 0°

Solid jet for very stubborn dirt and stains.

Order no. 2.884-534.0



Inno Foam Set

Inno Foam Set with RM injector

HP foam system for use with mobile and stationary HD/HDS units for cleaning and disinfection. Twin spray lance with foam nozzle and changeover to HP jet for clear rinsing etc., HP chemical injector with precision 0-5% metering valve. The machine specific nozzle kit has to be ordered separately.

Order no. 2.640-151.0



Longlife food industry version

High-pressure hose Longlife 400, 15 m, DN 6, AVS trigger gun connection

Longlife HP hose for use in the food industry. Außendecke## animal-grease-resistant, non-colour-bleeding material. With patented AVS connection in the pistol (pivot mounted)

Order no. 6.391-888.0



Machine-specific nozzle kit for HSC##

Nozzle pack for hard surface cleaners (machine-specific) 500 - 650 l/h

Machine-specific nozzle kit KÄRCHER power nozzle for hard surface cleaners

Order no. 2.640-401.0



Machine-specific nozzle kit with order no. 3.637-170

Machine-specific nozzle kit for order no. 3.637-170 HD 500-700 l/h

For HD 500 - 700 l/h. Consists of nozzle insert + HP power nozzle + union

Order no. 4.769-045.0



Nozzle kits for Inno/Easy Foam Set

Nozzle kit 055 for Inno/Easy Set 500 - 600 l/h

Optimal adaptation to different machine outputs for economic use.

Order no. 2.640-870.0



Nozzle pack for wet blasting attachment

Nozzle pack for wet blasting attachment 035

Consisting of wet-blasting nozzle and nozzle insert, only for use with wet-blasting attachment 4762-010/-022

Order no. 2.638-526.0



Nozzle union

Nozzle union

With protector for high-pressure and Power nozzles M 18 x 1.5

Order no. 5.401-210.0



Pipe cleaning hose, ID 6

Pipe cleaning hose, NW 6, 30 m

Especially flexible high-pressure hoses for inner pipe cleaning (thread connection for nozzle R 1/8).

Order no. 6.390-029.0



Pipe cleaning hose, NW 6, 20 m

Especially flexible high-pressure hoses for inner pipe cleaning (thread connection for nozzle R 1/8).

Order no. 6.390-028.0



Power nozzle spray angle 15°

Power nozzle spray angle 15°

Fan jet nozzle for stubborn dirt and stains.

Order no. 2.883-389.0



Power nozzle spray angle 25°

Power nozzle, spray angle 25°

Fan jet nozzle for large-area coverage and stubborn dirt and stains.

Order no. 2.883-829.0



Power nozzle spray angle 40°

Power nozzle spray angle 40°

Fan jet nozzle for large-area coverage – suitable for sensitive surfaces

Order no. 2.884-523.0



Push-on washing brush

Push-on washing brush, M18 x 1.5

General-purpose cleaning on all surfaces. With clamp for mounting directly to spray lance. Connection M 18 x 1.5.

Order no. 4.762-016.0



Push-on washing brush

With clamp for mounting directly to units' double or triple nozzle.

Order no. 4.762-328.0



Rotary coupling

Rotating coupler

Reliably prevents high-pressure hose twisting. Connection M 22 x 1.5 m. protector

Order no. 4.401-091.0



Rotary coupling

Rotary coupling

Reliably prevents high-pressure hose twisting. Connection M 22 x 1.5 m. protector

Order no. 4.401-076.0



Rotating spray lances

Swivelling spray lance 1,050 mm

Spray lance, 1,050 mm, swivelling, ergonomical

Order no. 4.760-550.0



Spray lance, 2,050 mm, swivelling, ergonomical

Spray lance, 2,050 mm, swivelling, ergonomical

Order no. 4.760-366.0



1550mm Rotating spray lance

Spray lance, 1,550 mm, swivelling, ergonomical

Order no. 4.760-365.0



Spray lance, complete, 840 mm

Spray lance, 840 mm, swivelling, ergonomical

Order no. 4.760-560.0



Rotating washing brush

Rotating washing brush for machines <lt; 800 l/h

Driven by water jet. Gently removes fine dust and traffic film from all surfaces. Temperature resistant up to 80 °C. M 18 x 1.5. (replaceable brush element)

Order no. 4.762-288.0



Rotary wash brush

Driven by water jet. Gently removes fine dust and traffic film from all surfaces. Temperature resistant up to 80 °C. M 18 x 1.5. (replaceable brush element)

Order no. 4.762-284.0



Shut-off cock

Shut-off cock

Mounts to machine's high-pressure outlet. The shut-off cock simplifies handling of pipe cleaning hose using the shut-off cock's "on-off" functions which can be easily controlled on the machine.

Order no. 4.580-160.0



Spacer (including nozzle union)

Spacer (incl. nozzle union)

Guarantees constant safety clearance, e.g. for tyres and bodywork. Helps prevent damage to sensitive surfaces. Mounts directly to lance.

Order no. 5.394-294.0



Spray lance

Spray lance, 250 mm, does not pivot

##Stainless steel with hand screw union, does not pivot. With extended trigger guns

Order no. 4.760-058.0



Spray lances

Double spray lance 960 mm

Infinitely adjustable control of the working pressure directly on the handle with full water quantity. Suitable above all for agriculture (e.g. cleaning stalls).

Order no. 6.394-665.0



standard

High-pressure hose, 10 m, DN 6, AVS gun connection Ø 11 mm

With patented AVS connection in the trigger gun (pivot-mounted) and hand screw union. M 22 x 1.5 with anti-kink protection. NW 6/155°C/250 bar

Order no. 6.391-238.0



High-pressure hose, 15 m DN 6, AVS trigger gun connection

With patented AVS connection in the trigger gun (pivot-mounted) and hand screw union. M 22 x 1.5 with anti-kink protection. NW 6/155°C/250 bar

Order no. 6.390-174.0



High-pressure hose, 10 m DN 6, AVS trigger gun connection

With patented AVS connection in trigger gun (pivot mounted) and hand screw union. M22x1.5 with anti-kink protection ID 6/155°C/250 bar

Order no. 6.389-853.0



Standard with push-in nipple on both sides

HD hose DN6, 15m, for hose reels

With patented AVS connection in the trigger gun (pivot-mounted) and push-in nipple connection for the hose reel.

Order no. 6.391-172.0



Starting current limiter

Starting current limiter

Reduces starting current in single-phase supply and protects line fuse.

Order no. 2.637-495.0



Stationäre Hochdruckanlagen

High-pressure hose, 1.5 m DN 8, connection to hose reel

Order no. 6.388-886.0



Suction filter

Suction filter without non-return valve

Without non-return valve, brass

Order no. 4.730-019.0



Suction filters with non-return valve

With non-return valve, brass

Order no. 4.730-012.0



Triple nozzle, touchless changeover

Triple nozzle, touchless changeover

Quick and convenient spray jet changeover by swivelling the nozzle. Choose from high-pressure pencil jet, high-pressure fan jet (25°), manual changeover to low pressure fan jet (40°). On machines with injector, the low-pressure fan jet is used for picking up and applying detergent. M18 x 1.5 connection.

Order no. 4.767-002.0



Triple nozzles

Triple nozzle 043

Order no. 4.767-152.0



Undercarriage spray lance

Underbody lance

Mobile. For effective and convenient cleaning of underbodies, chassis and wheel arches. Stainless steel. Without HP nozzle.

Order no. 4.760-245.0



Variable pressure spray lance

Variable pressure spray lance, 670 mm

With integrated pressure gauge for infinitely variable pressure control directly on the spray lance. Nozzle union M 24 x 1.5. Addition of cleaning agent at low pressures.

Order no. 4.760-362.0



Variable pressure spray lance, 1,040 mm

With integrated pressure gauge for infinitely variable pressure control directly on the spray lance. Nozzle union M 24 x 1.5. Addition of cleaning agent at low pressures.

Order no. 4.760-230.0



Water supply hose

Water supply hose

NW 19 R1" / R 3/4", up to 85 °C, for pick-up

Order no. 4.440-207.0



Water supply hose

Water supply hose

NW 13 R1" / R 3/4", up to 30 °C

Order no. 4.440-038.0



Wet blasting attachment (without nozzle)

Wet blasting attachment without flow control (without nozzle)

Adds abrasive to high-pressure jet. For removing paint, rust, scaling. Mounts to spray lance instead of the of high-pressure nozzle. Without flow control.

Order no. 4.762-022.0



Wet blasting attachment with flow control (without nozzle)

Adds abrasive to high-pressure jet. For removing paint, rust, scaling. Mounts to spray lance instead of the of high-pressure nozzle. With flow control.

Order no. 4.762-010.0

